

Petrol-Seal

Petrol Seal paste is a fuel resistant sealant used primarily as a flange bonder for Blueline entry fittings. This material is designed for petroleum secondary containment sealing applications.

FEATURES & BENEFITS

- Petrol-Seal has a service range from -20°F to 200° F
- Used with KFD Series Fittings on Poly or Fiberglass single wall sumps

Curing

Once mixed the sealant begins curing and has a ONE HOUR application life @77°F. The sealant will cure faster at higher temperatures up to 95°F and slower at cooler temperatures to 45°F. If the surface temperatures of the substrates are outside this range, do not use the sealant until the temperature changes

Petrol Seal is available in four different forms

- 1.5 gallon bucket - For large multiple installations
- 1 qt. bucket - For individual sump installations
- 200 ml Dual Tube (dispensing gun sold separately) (5 Kwik Fits)
- 400 ml Dual Tube (dispensing gun sold separately) (10 Kwik Fits)



Part Number	Description
ACB010	Petrol-Seal Paste - 1.5 gallon
ACB011	Petrol-Seal - 1 Quart
ACB019	Petrol-Seal - 200 ml Tube (Includes 2 Static Mixers)
ACB020	Petrol-Seal -400 ml Tube (Includes 3 Static Mixers)
ACB022	Petrol-Seal Static Mixer
ACB021	Petrol-Seal Manual Dispensing Gun (Works with 200 ml & 400 ml Tubes) NET PRICE
ACB021A	Petrol-Seal Pneumatic Dispensing Gun (Works with 200 ml & 400 ml Tubes) NET PRICE



Manual and Pneumatic Petrol Seal Delivery System

The Petro-Seal delivery systems quickly and easily dispense Petro-Seal during the installation of Blueline Fittings. The guns work for both 200 and 400 ml twin tubes. Choose the Pneumatic gun for easier dispensing on large sites with multiple fittings.